

► CAREL QUICK START GUIDE



Frigbot® was made to work with Carel®. The installation and configuration of your new Frigbot are really easy. If you're a licenced tradesperson you can also install the additional current sensor that allows you to read the power usage and set alerts for when something is going wrong, more about this later.

► This is what you will need

1. Smartphone
 2. Frigbot Device
 3. Your Equipment which has a Carel controller fitted
 4. (Optional) A few connectors and some mains power cable
- ** Important iPhone must use Safari Browser and Android must use Chrome Browser

► OPTIONAL ATTACH 3dbi ANTENNA

If the Frigbot is located where there is weak cellular connectivity, you can purchase the extended remote antenna (3db gain) which is sold separately.

► PLUG-IN CONTROLLER

Turn the power off to your controller.
Plug the Red Cable into the Carel controller.
Use the end that has the 4 pin connector



► ENSURE IT IS FULLY PLUGGED IN

You may need to use a pen to push it all the way into the plug



▶ **OPTIONAL CURRENT SENSOR**

Pass the compressor power cable (or the main power supply cable) through the Frigbot current sensor this is for qualified tradespersons ONLY



▶ **SCAN QR CODE**

1. Login to the Frigbot website on your smartphone <https://frigbot.com/login>
2. Open the 'Frigbots' tab
3. Select 'Scan Frigbot'

** Important iPhone must use Safari Browser and Android must use Chrome Browser



▶ **CONFIGURE**

Register and Configure your new Frigbot:

1. **Choose a connection PLAN**
2. **Authorise PAYMENT**
3. **CONTACT NAME** who owns the equipment?
4. **EQUIPMENT NAME** what is the Frigbot plugged into?
5. **ALERTS and REPORTS** (optional) can be set up after a full sync

▶ **RELAX**

It will now take about 20 minutes for your Frigbot to collect enough Carel Data to enable a full sync with the Frigbot cloud application.

